

ALTO Internal Sounder

Low profile sounder, speaker or combined sounder/speaker



SP/ALTO/WH Extension Speaker

- Low Profile Design
- Tamper protected lid and mounting
- Dynamic piezo technology
- High Impedance allowing multiple speakers to be used
- Does not require any 12volt power supply

SOSP/ALTO/WH/G

Combined Internal Sounder and Extension Speaker

- Low Profile Design
- 110dB(A) sound output
- Connect either as a sounder or speaker
- Selectable alternating or continuous tone
- Low current consumption
- Tamper protected lid and mounting
- High Impedance allowing multiple speakers to be used

SO/ALTO/WH/G Internal Sounder

- Low Profile Design
- 110dB(A) sound output
- Selectable alternating or continuous tone
- Low current consumption
- Tamper protected lid and mounting

3rd Party Tested

TECHNICAL SPECIFICATIONS

Internal Sounder	
Nominal Power Supply:	6-14V DC
Current Draw:	120mA MAX.
Sound Output:	110dB(A)
Colour:	White
Tamper:	Cover & Wall
Material:	ABS
Dimensions:	115 x 115 x 32mm
Product Code:	SO/ALTO/WH
EN Grade:	3
Environmental Class:	II

Extension Speaker	
Nominal Impedance:	Better than 16 ohms
Speaker Type:	Tone (Piezo)
Sound Output Level:	>100 dB(A) @ 1 metre
Temperature Range:	White
Tamper:	Cover & Wall
Material:	ABS
Dimensions:	115 x 115 x 32mm
Product Code:	SP/ALTO/WH

Combined Internal Sounder and Extension Speaker

Internal Sounder:	As specifications above
Extension Speaker:	As specifications above
Product Code:	SOSP/ALTO/WH/G

